

# JSON-BASED ACCOUNTS IMPORT

## STRUCTURE

To import accounts and their users into ScheduleInterpreter® prepare information utilizing JSON-structured file, formatted using array of users and their corresponding information.

 "\_comment" key is always ignored during import.

```
[{
  "account": {
    "_comment": "general user information",
    "name": "General hospital",
    "timeZoneID": "2",
    "registerDate": "2012-01-01 03:00:00",
    "eMail": "michael.smith@gmail.com",
    "si_id": "98765"
  },
  "accountContact": [{
    "_comment": "Account's contact info, populates on Schedule Interpreter form",
    "street": "123 Main Street",
    "city": "Happy town",
    "state": "CA",
    "zip": "90210",
    "country_code": "US"
  }],
  "locations": [{
    "_comment": "Location where interpreting takes place",
    "name": "Cardiology",
    "street": "123 Main Street",
    "city": "Happy town",
    "state": "CA",
    "zip": "90210",
    "country_code": "US"
  }],
  "users": [{
    "user": {
      "_comment": "general user information",
      "fName": "Michael",
      "lName": "Smith",
      "userName": "michael.smith.123",
      "eMail": "michael.smith@gmail.com",
      "si_id": "98765"
    },
    "userContact": [{
      "_comment": "User address, will be used on invoice, when userType is set to 200 or 100",
      "street": "123 Main Street",
      "city": "Happy town",
      "state": "CA",
      "zip": "90210",
      "country_code": "US"
    }],
    "integration_code": [{
      "_comment": "user's codes in third party platforms",
      "platform_id": "2",
      "code": "12346",
      "field": "CLIENT_ID",
      "label": "Oracle Fusion client ID"
    }],
    "integration_code": [{
      "_comment": "account's codes in third party platforms",
      "platform_id": "2",
      "code": "12346",

```

```

"field": "ACCOUNT_ID",
"label": "Oracle Fusion account ID",
"import_column": "18",
"export_column": "23"
}, {
  "_comment": "account's codes in third party platforms",
  "platform_id": "2",
  "code": "547865",
  "field": "SHIP_TO_CONTACT_PARTY_NUMBER",
  "label": "Ship-to Contact Party Number",
  "import_column": "14",
  "export_column": "36"
}]
}]

```

## KEYS AND DATA SECTIONS

**account** parent key contains general information about the account

| Key          | Description   | Type                     | Mandatory |
|--------------|---|--------------------------|-----------|
| name         | Account name  | String                   | Yes       |
| timeZoneID   | Time zone ID (account HQ)   | Integer                  | Yes       |
| isDaylight   | Flags account is in the location that supports daylight saving time | Integer: 0 - no, 1 - yes | Yes       |
| registerDate | Date when account was created                                       | String                   | No        |
| masterID     | ID of the master account generated by ScheduleInterpreter®          | Integer                  | No        |
| url          | Website of the account  | String                   | No        |



When two tier structure is imported the first time, master accounts must be imported first. Sub-account imported in second upload, using **masterID** key generated by ScheduleInterpreter® after initial import.

**accountContact** parent key contains address information. This information is populating in the Schedule Interpreter form, when request for services is being made.

| Key          | Description    | Type   | Mandatory |
|--------------|----------------|--------|-----------|
| street       | Street address | String | Yes       |
| city         | City           | String | Yes       |
| state        | State          | String | Yes       |
| zip          | Postal code    | String | Yes       |
| country_code | Country code   | String | Yes       |

**locations** parent key contains information associated with locations of the account. This information is presented as multiple choice in the Schedule Interpreter form, when request for services is submitted. Address association

with the location name is populating in the form, when request for services is being made.

| Key          | Description    | Type   | Mandatory |
|--------------|----------------|--------|-----------|
| name         | Location name  | String | Yes       |
| street       | Street address | String | Yes       |
| city         | City           | String | Yes       |
| state        | State          | String | Yes       |
| zip          | Postal code    | String | Yes       |
| country_code | Country code   | String | Yes       |

**users** parent key contains general information about users

| Key          | Description                            | Type             | Mandatory |
|--------------|--|------------------|-----------|
| title        | User title (Mr., Mrs., etc.)           | String           | No        |
| fName        | User first name                        | String           | Yes       |
| lName        | User last name                         | String           | Yes       |
| occupation   | Position, title, occupation            | String           | No        |
| userName     | User name used for login               | String           | Yes       |
| eMail        | User e-mail address                    | String           | Yes       |
| registerDate | Registration date                      | Date: yyyy-mm-dd | No        |
| comments     | Comments                               | Text             | No        |
| password     | User password (not encrypted)          | String           | No        |
| userType     | Type of the user profile (default 102) | Integer          | No        |
| si_id        | ID assigned by ScheduleInterpreter®    | Integer          | No        |



**si\_id** key is required for update process.

**userContact** parent key contains up to two contact entries. Using is\_business flag, import process will configure and secondary address for a vendor.

| Key    | Description    | Type   | Mandatory |
|--------|----------------|--------|-----------|
| street | Street address | String | Yes       |
| city   | City           | String | Yes       |

|              |                 |         |     |
|--------------|-----------------|---------|-----|
| state        | State           | String  | Yes |
| zip          | Postal code     | String  | Yes |
| country_code | Country code    | String  | Yes |
| phAC         | Phone area code | Integer | No  |
| phPref       | Phone prefix    | Integer | No  |
| phSuf        | Phone suffix    | Integer | No  |
| phExt        | Phone extension | Integer | No  |
| cellAC       | Cell area code  | Integer | No  |
| cellPref     | Cell prefix     | Integer | No  |
| cellSuf      | Cell suffix     | Integer | No  |

---

🔄Revision #4

★Created Thu, Apr 9, 2020 11:51 AM by manual admin

✎Updated Tue, May 19, 2020 3:52 PM by manual admin